

Beckers



Becker Acroma

SAFETY DATA SHEET

Date of issue/ Date of revision : 2010-10-11.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Product name : Lacroma Clear 25

Product code : EM1157-0025

Use of the substance/preparation

Product use : Industrial applications, Used by spraying.

Company/undertaking identification

Manufacturer : Becker Acroma KB
 Bellö, SE-570 32 Hjärtevad, SWEDEN
 Tel: +46 (0)381 261 00
 Fax: +46 (0)381 261 95
 info@beckeracroma.com

e-mail address of person responsible for this SDS : SDS@beckeracroma.com

Supplier : Becker Acroma spol. s r.o.
 Družstevní 56
 CZ - 594 01 Velké Meziříčí
 IČO: 49447301
 Tel: +420 566 501 411, fax: +420 566 520 310
 info@becker-acroma.cz

Emergency telephone number of the company : Becker Acroma, +46 (0)381 262 59, +46 (0)381 262 34, +46 (0)381 262 07

Emergency telephone number : Toxikologické informační středisko
 Na bojišti 1, CZ - 128 21 Praha 2
 tel. +420 224 919 293

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

Additional warning phrases : Safety Data Sheet available for professional user on request.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Chemical name	CAS number	EC number	%	Classification
Butyl glycol	111-76-2	203-905-0	1-2,5	Xn; R20/21/22 [1] [2]
Butyl diglycol	112-34-5	203-961-6	1-2,5	Xi; R36/38 [1] [2]
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 5 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Extinguishing media not to be used** : Do not use water jet.
- Special exposure hazards** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Due to the organic solvents content of the preparation:

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).
- Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
- Methods for cleaning up** : Preferably clean with a detergent. Avoid using solvents.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

- Handling** : Due to the organic solvents content of the preparation:
- Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel.
- Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth,

7. HANDLING AND STORAGE

ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

Storage : Store in accordance with local regulations. Observe label precautions. Do not store below the following temperature: 5°C (41°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Due to the organic solvents content of the preparation:
Keep away from sources of ignition. Keep away from: oxidizing agents, strong alkalis, strong acids.
No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Czech Republic - Storage code : IV

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient name

Butyl glycol

Occupational exposure limits

178/2001 (Czech Republic, 12/2007). Absorbed through skin.

STEL: 200 mg/m³ 15 minute(s).

STEL: 41,4 ppm 15 minute(s).

TWA: 100 mg/m³ 8 hour(s).

TWA: 20,7 ppm 8 hour(s).

Butyl diglycol

178/2001 (Czech Republic, 12/2007).

TWA: 70 mg/m³ 8 hour(s).

TWA: 10,57 ppm 8 hour(s).

STEL: 100 mg/m³ 15 minute(s).

STEL: 15,1 ppm 15 minute(s).

Exposure controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Occupational exposure controls

Respiratory system : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Recommended : particulate filter, P2-P3

Skin and body : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

Hands : Wear suitable gloves. Recommended: Silver Shield gloves.
The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Composition/information on ingredients. breakthrough time: Please contact your glove supplier to get the information.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid.

Flash point : Closed cup: 102°C (215,6°F) [ASTM 6450]

Viscosity : 60-70 s DIN4

Relative density : 1,03 g/cm³

Explosion limits : Lower : 0.8%-v/v, upper : 12.7%-v/v.

VOC content : 5 %
48 (g/l).

Dry content (%) : 33

Gloss (G60°) : 22-27

10. STABILITY AND REACTIVITY

- Conditions to avoid** : Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.
- Materials to avoid** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Toxicokinetics

- Distribution** : Contains material which may cause damage to the following organs: blood, kidneys, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butyl glycol	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LC50 Inhalation Vapor	Rat	2900 mg/m ³	7 hours
	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
Butyl diglycol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	5660 mg/kg	-

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Butyl glycol	-	Acute EC50 >1000 mg/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
	-	Acute LC50 >1000 mg/L Marine water	Crustaceans - Amphipod - Chaetogammarus marinus - Young - 5 mm	48 hours
	-	Acute LC50 1490000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 33 to 75 mm	96 hours
	-	Acute LC50 1250000 ug/L Marine water	Fish - Inland silverside - Menidia beryllina - 40 to 100 mm	96 hours
	-	Acute LC50 800000 to 1000000 ug/L Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon	48 hours
	-	Chronic NOEC	Daphnia - Water	

12. ECOLOGICAL INFORMATION

		1000 mg/L Fresh water	flea - Daphnia magna - <24 hours	
Butyl diglycol	-	Acute LC50 2000000 ug/L Marine water	Fish - Inland silverside - Menidia beryllina - 40 to 100 mm	96 hours
	-	Acute LC50 1300000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 33 to 75 mm	96 hours

Ecological information

<u>Product/ingredient name</u>	<u>Aquatic half-life</u>	<u>Photolysis</u>	<u>Biodegradability</u>
Butyl glycol	-	-	Readily
Butyl diglycol	-	-	Readily

Bioaccumulative potential

<u>Product/ingredient name</u>	<u>LogP_{ow}</u>	<u>BCF</u>	<u>Potential</u>
Butyl glycol	0,83	-	low
Butyl diglycol	0,6	2,9	low

PBT : Not available

vPvB : Not available

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

European Waste Catalogue : 08 01 12

(EWC):

Hazardous waste : No.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Land - road/railway

Transport document name : -

Packing group : -

Sea

Proper shipping name : -

Special provisions : Not available

Marine pollutant substances : Not available

Packing group : -
Not available

Marine pollutant : No.

Emergency schedules (EmS) : Not available

Air

Proper shipping name : -

Special provisions : Not available

Packing group : -

Proper shipping name : -

Packing group : -

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

15. REGULATORY INFORMATION

- EU regulations** : The product is determined as not being dangerous according to the requirements of the DPD.
- Risk phrases** : The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Other EU regulations

- Additional warning phrases** : Safety Data Sheet available for professional user on request.

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

- Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

16. OTHER INFORMATION

- Full text of R-phrases referred to in sections 2 and 3 - Czech Republic** : R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.
R36- Irritating to eyes.
R36/38- Irritating to eyes and skin.

- Date of issue/ Date of revision** : 2010-10-11.

- Date of printing** : 2010-12-07.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.